Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: ChiliTec GmbH

Supplier's address: -

Model identifier: 22093

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type	Wire					
(or other electric interface)						
Mains or non-mains:	MLS	Connected light source (CLS):	Nein			
Colour-tuneable light source:	Nein	Envelope:	-			
High luminance light source:	Nein					
Anti-glare shield:	Nein	Dimmable:	Yes			
Product parameters						

	Floduct parameters						
Parameter		Value	Parameter	Value			
General product parameters:							
Energy consum mode (kWh/100 up to the neares	0 h), rounded	5	Energy efficiency class	F			
Useful luminou indicating if it re in a sphere (36 cone (120 [°]) or in (90 [°])	fers to the flux 0°), in a wide	440 in Wide cone (120°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000			
On-mode po expressed in W	ower (P _{on}),	5,0	Standby power (P _{sb}), expressed in W and rounded to the second decimal	-			
Networked stand for CLS, express rounded to the s	sed in W and	-	Colour rendering index, rounded to the nearest integer, or the range of CRI- values that can be set				
Outer	Height	-	Spectral power	See image			
dimensions	Width	-	distribution in the	in last page			
without	Depth	-		Coite 1 / C			

separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-			
		Chromaticity coordinates (x and y)				
Parameters for LED and OLED light sources:						
R9 colour rendering index value	-	Survival factor	-			
the lumen maintenance factor	-					
Parameters for LED and OLED mains light sources:						
displacement factor (cos φ1)	-	Colour consistency in McAdam ellipses	-			
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	_(b)	If yes then replacement claim (W)	-			
Flicker metric (Pst LM)	-	Stroboscopic effect metric (SVM)	-			

(a)_{'-'} : not applicable;

(b)_{'-'} : not applicable;