



























Wireless Pan-Tilt IP Camera

The LogiLink WC0030A is an integrated wireless IP Camera solution. It combines a high quality digital Video Camera with network connectivity and a powerful web server to bring clear to your Desktop from anywhere on your local network or over the Internet.

The basic function of it is transmitting remote video on IP network. The high quality video image can be transmitted with 30fps speed on the LAN/WAN by using MJPEG hardware compression technology.

It is based on TCP/IP standard, build-in WEB server which could support Internet Explore. Therefore the management and maintenance of your device become more simply by using network to achieve the remote configuration, start-up and upgrade firmware.

Feature:

- Powerful high-speed video protocol processor
- High-sensitivity 1/4" CMOS sensor
- Picture total 300k pixels

LogiLink.

- Supports PT control, Pan 270°, Tilt 120°
- Optimized MJPEG video compression for transmission
- Multi-level users' management and passwords definition
- Supports wireless network (Wi-Fi/802.11/b/g/n)
- Supporting Dynamic IP (DDNS) and UPNP LAN and Internet (ADSL, Cable Modem)
- Giving alarm in cause of motion detection
- Supporting image snapshot
- Supports multiple protocols: HTTP/TCP/IP/UDP/ SMTP/DDNS/SNTP/DHCP/FTP
- Supports WEP/WPA/WPA2 encryption
- Supports 3G phone, Smart phone control
- Supports Firefox, Safari, Google chrome browser
- Supports Android and iPhone app
- Supports P2P function





































Art No. WC0030A

Wireless Pan-Tilt IP Camera

Specification:

Image Sensor	
Sensor	1/4" Color CMOS Sensor
Resolution	640 x 480 Pixels (300k Pixels)
IR Lens	f: 3.6mm, F2.0 (3.6mm lens is 90°)
Minimum Illumination	0.5Lux @ F2.0
Video/Image Setting	
Video Compression	MJPEG
Video Frame Rate	15fps(VGA), 30fps(QVGA)
Resolution	640 x 480(VGA), 320 x 240(QVGA)
Flip Mirror Images	Vertical / Horizontal
Light Frequency	50Hz, 60Hz or Outdoor
Video Parameters	Brightness, Contrast
Audio Talk-Back	Built-in Mic
Communication	
System Interface	10Base-T/100Base-TX Ethernet Port
Supported Protocol	TCP/IP, DHCP, SMTP, HTTP, DDNS, UPNP, PPPoE, FTP, DNS, UDP, GPRS
Wireless LAN	Supports wireless network (Wi-Fi/802.11/b/g/n)
WEP Encryption	Disable / 64 bit / 128 bit
WPA/WPA2 Encryption	TKIP / AES
Physical / Environmen	t
Power Supply	AC 5V/2A External Power Adapter
Power Consumption	5W (Max.)
Operate Temperature	0°C ~ 55°C (14°F~131°F)
Operate Humidity	20%-85% non-condensing
Storage Temperature	-10°C ~ 60°C (14°F ~140°F)
Storage Humidity	0%-90% non-condensing





^{*} The specifications and pictures are subject to change without notice.
*All trade names referenced are the registered namework of their respective owners.





























Wireless Pan-Tilt IP Camera

System Requirement:

LogiLink.

-	
CPU	2.0GHz or above
Memory Size	256MB or above
Display Card	64M or above memory
Supported OS	Microsoft Windows 98/ME/2000/XP/Vista/7/8
Browser	IE6.0, IE7.0, IE8.0, Firefox, Safari, Google chrome etc.



Front Panel of the Wireless Pan-Tilt IP Camera

- 1. IR Sensor
- 2. Infrared LED
- 3. Loud Speaker
- 4. LENs
- 5. Network Indicator LED
- 6. Microphone

Built-in motorizes Pan/Tilt with viewing angle 270° horizontally and 120° vertically



Rear Panel of the Wireless Pan-Tilt IP Camera

- 1. Audio Output
- 2. LAN Port
- 3. Antenna
- 4. IO Alarm Port
- 5. DC Power





^{*} The specifications and pictures are subject to change without notice. *All trade names referenced are the registered namework of their respective owners.





























Art No. WC0030A

Wireless Pan-Tilt IP Camera

Package Content:

- 1 x Wireless IP Camera
- 1 x Wi-Fi Antenna
- 1 x Power Adapter
- 1 x Network Cable
- 1 x Mounting Bracket
- 1 x CD-ROM (Software & Manual)
- 1 x Quick Installation Guide



Packaging Information:

• Packing Dimension: 190 x 120 x 175mm

• Packing Weight: 0.65kg

• Carton Dimension: 395 x 255 x 185mm

Carton Q'ty: 4pcsCarton Weight: 3kg





P2P IPCamera

Free APP P2P IPCamera available to download:







For Android



