

- 1. CABLE: 32AWG, 20C
- 2. CONNECTORS: HDMI19P MALE*1PCS, HDMI19P FEMALE*1PCS(BLACK INSULATOR) Gold Plated
- 3. MOLD: ASS'Y TYPE.
- 4. CONTACTS:

| HDMI(M) | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | SHELL |
|---------|---|---|---|---|---|---|---|---|---|----|----|----|----|----|----|----|----|----|----|-------|
| HDMI(F) | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 | 9 | 10 | 11 | 12 | 13 | 14 | 15 | 16 | 17 | 18 | 19 | SHELL |

5. OPEN/SHORT TEST: 100% TEST.

A.100% OPEN,SHORT&INTERMITANCE TEST. B.CONDUCTOR RESISTANCE: 3ohms MAX: C.INSULATION RESISTANCE: 5M Min/,10ms:

6. ALL MUST BE MEET ON ROHS COMPLIANT.

Sticker ex:



Pantone 2945C Black Size: 50 x 35 mm R= 2mm

| COMPANY | | | ITEM NO. | AH0011 | NO | В | Part Name | | | | |
|----------|------|-------------|----------------|--------|-----|----------|-------------|--------|-------------|---------------|--------------|
| REVISION | DATE | DISCRIPTION | DRAWN | | HDI | /Ι Δ Τνη | e Male to | | | SCALE | |
| REV.A/0 | | | BY DESIGNED | | Fem | | e iviale to | 2direc | t GmbH | UNIT(mm) | |
| | | | BY | | | | | Zance | ,t dilibili | ONI I (IIIII) | $ \Psi \cup$ |
| | | | APPROVAL BY | | | | | | | PAGE | 1/1 |