



# VU+ UNO 4K SE

Your **Smart Linux TV Player**

Mit der **VU+ UNO 4K SE** bietet **VU+** UHD für jedermann. Der flexible Tuner erlaubt den Einsatz in jeder Empfangsumgebung. Wie von **VU+** gewohnt unterstützt dieser günstige UHD Receiver alle Features die das Benutzerherz höher schlagen lassen. Unglaublich schnelle Umschaltzeiten, HDMI IN, PVR ready, Farb Display sind ebenso wie HbbTV und Transcoding selbstverständlich.

Dual-Core-Prozessor  
1.7 GHz

+ 1x Plug&Play FBC DVB-S2(X) oder  
FBC DVB-C oder Dual DVB-T2 Tuner

+ 4 GB Flash, 2 GB RAM

+ 2,4" Farb LCD

HDMI 2.0  
OUT/IN

+ HD Transcoding

+ PVR (2.5" HDD)  
(Detachable)

+ externes Netzteil

1 x Common Interface

+ 1 x Smartcard

+ HbbTV



# Vu+ UNO 4K SE

Your **Smart** Linux TV Player



## Technische Daten



Front Panel	Display	2,4" Color LCD Display displaying channel names and program information, pictures and picons
	Key	„1 Touch“
Rear Panel	Tuner	DVB-S2(X) FBC or DVB-C FBC(8demod) or DUAL T2
	Video/Audio output (digital)	1 x HDMI 2.0
	Video/Audio in (digital)	1 x HDMI
	Audio output (digital)	Standard optical (SPDIF)
	Smart card slot	1
	Common Interface	1
	USB 3.0	2
	Gigabit-Ethernet	1
	External IR Sensor	1
	RS 232	1
	HDD	Plug&Play 2,5"
Power	Main voltage	100-240 V / 50-60 Hz
	Power consumption (typ. Operation/ Stand-by)	15 W / 0,5 W
RF	RF range DVB-S2/DVB-C	47-864 MHz / 950-2,150 MHz
	FEC, de-multiplexer	DVB-S/DVB-S2/DVB-C/T2
Video	Video Resolution	576p, 720p, 1080i, 1080p, 2160i, 2160p
	Video decoding	H.264/MPEG-4 AVC MVC H.265/HEVC MP
	Input data rate	2-45 MSymb/s
	S/N	>53dB
	Decoding	AC3, MPEG-4 (AAC-HE), MPEG-1, Layer 1, 2 and 3
Audio	Sampling rate	32/44.1/48 kHz
	S/N	>65 dB
LNB	LNB power supply	14V/18V (Max. 400mA)
	Control Signal	22kHz; ToneBurst; DiSEqC 1.0/1.1/1.2; USALS
General	Dimensions (W x H x D)	280mm x 195mm x 45mm
	Weight	~2kg
	Remote	Universal Remote