

Power-Line



LED Arbeitsleuchte TWIN POWER

- 1 x Schutzkontaktsteckdose (max. 3500 W)
- Klappbar als Transportschutz
- Bis zu 290° klappbar / aufklappbar
- Tragegriff
- Energieeffizienzklasse: A+
- Schutzart: IP 54 (bei geschlossenem Klappdeckel); IP 44 (bei geöffnetem Klappdeckel)
- Leuchtmittel: 2 x 20 W LED
- 2 x 1600 Lumen, 6000 Kelvin
- Abmessungen (BxHxT): ca. 185 x 280 x 115 mm
- Vorschaltgerät: LED-Treiber
- Lebensdauer: 30.000 h
- Zuleitung: 300 cm (H07RN-F 3G1,5 mm²)
- Farbwiedergabeindex RA: ≥ 80
- Abstrahlwinkel: 100°
- Schutzklasse: I
- Nenndaten: 230 V~; 50 Hz; 0,2 A
- Umgebungstemperatur: -25° C bis +50° C

LED worklight TWIN POWER

- 1 x safety socket (max. 3500 W)
- foldable as transport protection
- foldable up to 290°
- carrying handle
- energy efficiency category: A+
- protection type: IP 54 (with closed hinged cover); IP 44 (with open hinged cover)
- illuminant: 2 x 20 W LED
- 2 x 1600 Lumen, 6000 Kelvin
- dimensions (WxHxD): approx. 185 x 280 x 115 mm
- electronic control gear: LED-driver
- lifetime: 30,000 h
- cable: 300 cm (H07RN-F 3G1.5 mm²)
- colour rendering index RA: ≥ 80
- transmission angle: 100°
- protection class: I
- nominal voltage: 230 V~; 50 Hz; 0.2 A
- ambient temperature: -25° C up to +50° C

IP54

LED

2610100220

grau-orange
grey-orange

Karton
box

VE 1
PU 1

