

LogiLink®



USB-C™ to HDMI Multiport Adapter

Art. No.: UA0258

The USB-C™ to HDMI Multiport Adapter lets you connect your MacBook with a USB-C™ port to an HDMI display, while also connecting a standard USB3.0 device and a USB-C™ charging cable.

This adapter allows you to mirror your MacBook or Chromebook display to your HDMI-enabled TV or display in up to 1080p at 60Hz.


Simply connect the adapter to the USB-C™ port on your MacBook or Chromebook, and then to your TV or projector via an HDMI cable (sold separately).

Use the standard USB port to connect devices such as your flash drive or camera or a USB cable for syncing and charging your smart phones.

You can also connect a charging cable to the USB-C™ port to charge your MacBook, or Google Chromebook or other USB-C™ supported devices.

Features:

- » Supports USB-C™ input, and USB and HDMI output
- » Supports DisplayPort 1.2 Alt-mode
- » Supports USB 3.1 Gen1 super speed (5 Gbps) transmission, downward compatible USB 2.0
- » USB A port supports simultaneous charging and transmission of data for USB devices
- » Supports HDMI resolution up to 1080P @60Hz
- » Supports both video and audio output
- » USB-C™ female port supports USB Power Delivery Profile 4 up to 60W (20V/3A)
- » Supports simultaneous charging to your MacBook or Google Chromebook, or any other USB-C™ supported devices
- » Easy to use and carry



UA0258



Made in China



RoHS
compliant



*Specifications are subject to change without prior notice.

*USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum.

*All trade names referenced are the registered namework of their respective owners.

LogiLink®



USB-C™ to HDMI Multiport Adapter

Art. No.: UA0258

Specification:

Input	1x USB-C™ Male 1x USB-C™ Female for charging
Output	1x HDMI Female 1x USB A Female
HDMI Resolutions	Up to 1080P @60Hz
USB A Port	USB 3.1 Gen1 Super Speed up to 5 Gbps
USB-C™ Standard	USB 3.1 Gen1 (Thunderbolt™ 3 compatible)
Operating Temperature	0°C - 45°C
Operating Humidity	10 - 85% RH (no condensation)
Storage Temperature	-10°C - 70°C
Storage Humidity	5 - 90% RH (no condensation)
USB A female Port	Up to 5W (5V/1A)
USB-C™ Female Charging Port	USB PD Profile 4 Source up to 60W (20V/3A)
Product Dimension	59,1 x 40,2 x 14,1 mm
Product Weight	30g
Cable Length	14 cm

Compatible Devices:

Apple	2015 MacBook 2016 MacBook 2016 MacBook Pro
Dell	XPS 13
Google	Chromebook Pixel
HP	Elite x2 1012 G1 Pro Tablet 608
Samsung	900X5L-K01



Package Contents:

- » 1x USB-C™ to HDMI Multiport Adapter
- » 1x User Manual

Package Informations:

- » Packing Dimension: 173 x 163 x 25mm
- » Packing Weight: 0.085kg
- » Carton Dimension: 520 x 366 x 185mm
- » Carton Q'ty: 40pcs
- » Carton Weight: 4.3kg



UA0258



Made in China



RoHS
compliant



*Specifications are subject to change without prior notice.

*USB Type-C™ and USB-C™ are trademarks of USB Implementers Forum.

*All trade names referenced are the registered trademark of their respective owners.