

# JVS-H302-A2

### 2.0MP Dual Antenna Wi-Fi Camera



















## **Key Features**

- Resolution 1920\*1080
- With IR LED and IR-CUT, monitoring day and night
- Supports CloudSEE Int'l APP on iOS/Android
- Two-way talk
- Dual antenna 2.4Ghz Wi-Fi and 10/100M RJ45 Port
- Motion Detection
- IP66 Housing

### Dimensions(mm)





## **Specifications**

Image Sensor	•	
Max Resolution	Video	
Effective Pixels Compression Standard Maximum Frame Rate SNR(dB) S5.7db Bit Rate Illumination OLux (IR ON) Lens Lens Fixed 4 mm Viewing Angle IR-LEDs IR-LEDs IR-Distance Function Motion Detection Email Alert Day& Night Support Storage Pan/Tilt Audio Input Audio Codec Support (G711A/G711U) Privacy Mask Exposure Control Image Adjustment Auto. White Balance Image Rotation Support Stream Protocols Stream  2x Streams Wi-Fi Candard Dimensions(W*H*D) Weights(g) Material Motay Support Day® Night Support MH25 Support MH25 Support MH26 Support MH26 Support MH27 Support MH27 Support MH27 Support MH37 Support MH38 Support MH38 Support MH39 Support MH39 Support MH39 Support MH47 Support MH38 Support MH38 Support MH38 Support MH38 Support MH38 Support MH39 Support MH39 Support MH39 Support MH39 Support MH30 Support MH39 Support MH39 Support MH39 Support MH39 Support MH30 Suppo		1/ 2.7" CMOS
Compression Standard   Maximum Frame Rate   20fps   SNR(dB)   55.7db	Max Resolution	1920 x 1080
Maximum Frame Rate SNR(dB) S5.7db Bit Rate 40~8192 Kbps Illumination 0Lux (IR ON) Lens Lens Fixed 4 mm Viewing Angle IR-LEDS IR-Distance 15 Meters Function Motion Detection Email Alert Day& Night Support Storage Micro SD Card (Up to 128G) Pan/Tilt Not Support (Built-in Mic) Audio Input Audio Codec Support (G711A/G711U) Privacy Mask Exposure Control Image Adjustment Auto. White Balance Image Rotation Support Support Support Support Support Support Support Auto. White Balance Image Rotation Support Support Network Ethernet 10M/100M Ethernet, RJ45 Port Protocols HTTP, TCP/IP, UDP, ICMP, SMTP, DHCP, DNS Stream 2x Streams Wi-Fi 2.4Ghz LAN Support Smart Phone iOS/Android General Dimensions(W*H*D) Meights(g) Material Morking Temperature -20°C~55°C Humidity RH 10%~90% Power Supply DC12V/1A Consumption Day ≦ 3W Night ≦ 6W Installation Wall/Ceiling Bracket Mounting	Effective Pixels	2MP
SNR(dB) 55.7db  Bit Rate 40~8192 Kbps  Illumination 0Lux (IR ON)  Lens Fixed 4 mm  Viewing Angle H: 87.4°, V: 47°, D: 104°  IR-LEDS 18 LEDS  IR-Distance 15 Meters  Function  Motion Detection Support  Email Alert Support  Day& Night Support  Storage Micro SD Card (Up to 128G)  Pan/Tilt Not Support (G711A/G711U)  Privacy Mask Support up 4 areas  Exposure Control Support  Image Adjustment Support  Auto. White Balance Support  Image Rotation Support (Mirror/Flip)  Two-Way Talk Support  Protocols HTTP, TCP/IP, UDP, ICMP, SMTP, DHCP, DNS  Stream 2x Streams  Wi-Fi 2.4Ghz  LAN Support  Smart Phone iOS/Android  General  Dimensions(W*H*D) 186.82*56.27*68.08 (mm)  Weights(g) 400g  Material Aluminum  Working Temperature -20°C~55°C  Humidity RH 10%~90%  Power Supply DC12V/1A  Consumption Day≦3W Night≦ 6W  Installation Wall/Ceiling Bracket Mounting	Compression Standard	H.265/H.264
Bit Rate	Maximum Frame Rate	20fps
Illumination	SNR(dB)	55.7db
Illumination	Bit Rate	40~8192 Kbps
Lens   Fixed 4 mm   Viewing Angle   H: 87.4°, V: 47°, D: 104°   IR-LEDS   18 LEDS   IR-Distance   15 Meters   Function   Motion Detection   Support   Email Alert   Support   Day& Night   Support   Storage   Micro SD Card (Up to 128G)   Pan/Tilt   Not Support (Built-in Mic)   Audio Input   Support (G711A/G711U)   Privacy Mask   Support up 4 areas   Exposure Control   Support   Image Adjustment   Support   Auto. White Balance   Support   Image Rotation   Support   FTP   Not Supported   Network   Ethernet   10M/100M Ethernet, RJ45 Port   Protocols   HTTP, TCP/IP, UDP, ICMP, SMTP, DHCP, DNS   Stream   2x Streams   Wi-Fi   2.4Ghz   LAN   Support   Smart Phone   iOS/Android   General   Dimensions(W*H*D)   186.82*56.27*68.08 (mm)   Weights(g)   400g   Material   Aluminum   Working Temperature   -20°C~55°C   Humidity   RH 10%~90%   Power Supply   DC12V/1A   Consumption   Day≦3W Night≦6W   Installation   Wall/Ceiling Bracket Mounting	Illumination	
Viewing Angle       H: 87.4°, V: 47°, D: 104°         IR-LEDs       18 LEDs         IR-Distance       15 Meters         Function       Support         Motion Detection       Support         Email Alert       Support         Day& Night       Support         Storage       Micro SD Card (Up to 128G)         Pan/Tilt       Not Support (Built-in Mic)         Audio Input       Support (Built-in Mic)         Audio Codec       Support (G711A/G711U)         Privacy Mask       Support up 4 areas         Exposure Control       Support         Image Adjustment       Support         Auto. White Balance       Support         Image Rotation       Support (Mirror/Flip)         Two-Way Talk       Support         FTP       Not Supported         Network       Ethernet       10M/100M Ethernet, RJ45 Port         Protocols       HTTP, TCP/IP, UDP, ICMP, SMTP, DHCP, DNS         Stream       2x Streams         Wi-Fi       2.4Ghz         LAN       Support         Smart Phone       iOS/Android         General       Dimensions(W*H*D)       186.82*56.27*68.08 (mm)         Weights(g)       400g	Lens	
IR-LEDS IR-Distance IR-Distan	Lens	Fixed 4 mm
IR-LEDS IR-Distance IR-Distan	Viewing Angle	H: 87.4°, V: 47°, D: 104°
Function         Motion Detection       Support         Email Alert       Support         Day& Night       Support         Storage       Micro SD Card (Up to 128G)         Pan/Tilt       Not Supported         Audio Input       Support (Built-in Mic)         Audio Codec       Support (G711A/G711U)         Privacy Mask       Support up 4 areas         Exposure Control       Support         Image Adjustment       Support         Auto. White Balance       Support         Image Rotation       Support (Mirror/Flip)         Two-Way Talk       Support         FTP       Not Supported         Network       Support         Ethernet       10M/100M Ethernet, RJ45 Port         Protocols       HTTP, TCP/IP, UDP, ICMP, SMTP, DHCP, DNS         Stream       2x Streams         Wi-Fi       2.4Ghz         LAN       Support         Smart Phone       iOS/Android         General       Dimensions(W*H*D)       186.82*56.27*68.08 (mm)         Weights(g)       400g         Material       Aluminum         Working Temperature       -20°C~55°C         Humidity       RH 10%~90%      <		
Motion DetectionSupportEmail AlertSupportDay& NightSupportStorageMicro SD Card (Up to 128G)Pan/TiltNot SupportedAudio InputSupport (Built-in Mic)Audio CodecSupport (G711A/G711U)Privacy MaskSupport up 4 areasExposure ControlSupportImage AdjustmentSupportAuto. White BalanceSupportImage RotationSupport (Mirror/Flip)Two-Way TalkSupportFTPNot SupportedNetworkEthernet10M/100M Ethernet, RJ45 PortProtocolsHTTP, TCP/IP, UDP, ICMP, SMTP, DHCP, DNSStream2x StreamsWi-Fi2.4GhzLANSupportSmart PhoneiOS/AndroidGeneralDimensions(W*H*D)186.82*56.27*68.08 (mm)Weights(g)400gMaterialAluminumWorking Temperature-20°C~55°CHumidityRH 10%~90%Power SupplyDC12V/1AConsumptionDay ≤ 3W Night ≤ 6WInstallationWall/Ceiling Bracket Mounting	IR-Distance	15 Meters
Motion DetectionSupportEmail AlertSupportDay& NightSupportStorageMicro SD Card (Up to 128G)Pan/TiltNot SupportedAudio InputSupport (Built-in Mic)Audio CodecSupport (G711A/G711U)Privacy MaskSupport up 4 areasExposure ControlSupportImage AdjustmentSupportAuto. White BalanceSupportImage RotationSupport (Mirror/Flip)Two-Way TalkSupportFTPNot SupportedNetworkEthernet10M/100M Ethernet, RJ45 PortProtocolsHTTP, TCP/IP, UDP, ICMP, SMTP, DHCP, DNSStream2x StreamsWi-Fi2.4GhzLANSupportSmart PhoneiOS/AndroidGeneralDimensions(W*H*D)186.82*56.27*68.08 (mm)Weights(g)400gMaterialAluminumWorking Temperature-20°C~55°CHumidityRH 10%~90%Power SupplyDC12V/1AConsumptionDay ≤ 3W Night ≤ 6WInstallationWall/Ceiling Bracket Mounting		
Email AlertSupportDay& NightSupportStorageMicro SD Card (Up to 128G)Pan/TiltNot SupportedAudio InputSupport (Built-in Mic)Audio CodecSupport (G711A/G711U)Privacy MaskSupport up 4 areasExposure ControlSupportImage AdjustmentSupportAuto. White BalanceSupport (Mirror/Flip)Image RotationSupport (Mirror/Flip)Two-Way TalkSupportFTPNot SupportedNetworkEthernet10M/100M Ethernet, RJ45 PortProtocolsHTTP, TCP/IP, UDP, ICMP, SMTP, DHCP, DNSStream2x StreamsWi-Fi2.4GhzLANSupportSmart PhoneiOS/AndroidGeneralDimensions(W*H*D)186.82*56.27*68.08 (mm)Weights(g)400gMaterialAluminumWorking Temperature-20°C~55°CHumidityRH 10%~90%Power SupplyDC12V/1AConsumptionDay ≤ 3W Night ≤ 6WInstallationWall/Ceiling Bracket Mounting		Support
Day& NightSupportStorageMicro SD Card (Up to 128G)Pan/TiltNot SupportedAudio InputSupport (Built-in Mic)Audio CodecSupport (G711A/G711U)Privacy MaskSupport up 4 areasExposure ControlSupportImage AdjustmentSupportAuto. White BalanceSupport (Mirror/Flip)Image RotationSupport (Mirror/Flip)Two-Way TalkSupportFTPNot SupportedNetworkHTTP, TCP/IP, UDP, ICMP, SMTP, DHCP, DNSStream2x StreamsWi-Fi2.4GhzLANSupportSmart PhoneiOS/AndroidGeneralDimensions(W*H*D)186.82*56.27*68.08 (mm)Weights(g)400gMaterialAluminumWorking Temperature-20°C~55°CHumidityRH 10%~90%Power SupplyDC12V/1AConsumptionDay ≤ 3W Night ≤ 6WInstallationWall/Ceiling Bracket Mounting		
StorageMicro SD Card (Up to 128G)Pan/TiltNot SupportedAudio InputSupport (Built-in Mic)Audio CodecSupport (G711A/G711U)Privacy MaskSupport up 4 areasExposure ControlSupportImage AdjustmentSupportAuto. White BalanceSupport (Mirror/Flip)Image RotationSupport (Mirror/Flip)Two-Way TalkSupportFTPNot SupportedNetworkHTTP, TCP/IP, UDP, ICMP, SMTP, DHCP, DNSStream2x StreamsWi-Fi2.4GhzLANSupportSmart PhoneiOS/AndroidGeneralDimensions(W*H*D)186.82*56.27*68.08 (mm)Weights(g)400gMaterialAluminumWorking Temperature-20°C~55°CHumidityRH 10%~90%Power SupplyDC12V/1AConsumptionDay≦3W Night≦ 6WInstallationWall/Ceiling Bracket Mounting		
Pan/TiltNot SupportedAudio InputSupport (Built-in Mic)Audio CodecSupport (G711A/G711U)Privacy MaskSupport up 4 areasExposure ControlSupportImage AdjustmentSupportAuto. White BalanceSupportImage RotationSupport (Mirror/Flip)Two-Way TalkSupportFTPNot SupportedNetworkHTTP, TCP/IP, UDP, ICMP, SMTP, DHCP, DNSStream2x StreamsWi-Fi2.4GhzLANSupportSmart PhoneiOS/AndroidGeneralDimensions(W*H*D)186.82*56.27*68.08 (mm)Weights(g)400gMaterialAluminumWorking Temperature-20°C~55°CHumidityRH 10%~90%Power SupplyDC12V/1AConsumptionDay ≤ 3W Night ≤ 6WInstallationWall/Ceiling Bracket Mounting		
Audio InputSupport (Built-in Mic)Audio CodecSupport (G711A/G711U)Privacy MaskSupport up 4 areasExposure ControlSupportImage AdjustmentSupportAuto. White BalanceSupport (Mirror/Flip)Image RotationSupport (Mirror/Flip)Two-Way TalkSupportFTPNot SupportedNetworkEthernet10M/100M Ethernet, RJ45 PortProtocolsHTTP, TCP/IP, UDP, ICMP, SMTP, DHCP, DNSStream2x StreamsWi-Fi2.4GhzLANSupportSmart PhoneiOS/AndroidGeneralDimensions(W*H*D)186.82*56.27*68.08 (mm)Dimensions(W*H*D)400gMaterialAluminumWorking Temperature-20°C~55°CHumidityRH 10%~90%Power SupplyDC12V/1AConsumptionDay≦3W Night≦6WInstallationWall/Ceiling Bracket Mounting		· · · · · · · · · · · · · · · · · · ·
Audio CodecSupport (G711A/G711U)Privacy MaskSupport up 4 areasExposure ControlSupportImage AdjustmentSupportAuto. White BalanceSupport (Mirror/Flip)Image RotationSupport (Mirror/Flip)Two-Way TalkSupportFTPNot SupportedNetworkEthernet10M/100M Ethernet, RJ45 PortProtocolsHTTP, TCP/IP, UDP, ICMP, SMTP, DHCP, DNSStream2x StreamsWi-Fi2.4GhzLANSupportSmart PhoneiOS/AndroidGeneralDimensions(W*H*D)186.82*56.27*68.08 (mm)Weights(g)400gMaterialAluminumWorking Temperature-20°C~55°CHumidityRH 10%~90%Power SupplyDC12V/1AConsumptionDay≦3W Night≦6WInstallationWall/Ceiling Bracket Mounting		
Privacy MaskSupport up 4 areasExposure ControlSupportImage AdjustmentSupportAuto. White BalanceSupport (Mirror/Flip)Image RotationSupport (Mirror/Flip)Two-Way TalkSupportFTPNot SupportedNetworkHTTP, TCP/IP, UDP, ICMP, SMTP, DHCP, DNSStream2x StreamsWi-Fi2.4GhzLANSupportSmart PhoneiOS/AndroidGeneralDimensions(W*H*D)186.82*56.27*68.08 (mm)Weights(g)400gMaterialAluminumWorking Temperature-20°C~55°CHumidityRH 10%~90%Power SupplyDC12V/1AConsumptionDay≦3W Night≦ 6WInstallationWall/Ceiling Bracket Mounting	<u> </u>	
Exposure ControlSupportImage AdjustmentSupportAuto. White BalanceSupport (Mirror/Flip)Image RotationSupport (Mirror/Flip)Two-Way TalkSupportFTPNot SupportedNetworkHTTPEthernet10M/100M Ethernet, RJ45 PortProtocolsHTTP, TCP/IP, UDP, ICMP, SMTP, DHCP, DNSStream2x StreamsWi-Fi2.4GhzLANSupportSmart PhoneiOS/AndroidGeneralDimensions(W*H*D)186.82*56.27*68.08 (mm)Weights(g)400gMaterialAluminumWorking Temperature-20°C~55°CHumidityRH 10%~90%Power SupplyDC12V/1AConsumptionDay≦3W Night≦ 6WInstallationWall/Ceiling Bracket Mounting		
Image AdjustmentSupportAuto. White BalanceSupportImage RotationSupport (Mirror/Flip)Two-Way TalkSupportFTPNot SupportedNetworkHTTPEthernet10M/100M Ethernet, RJ45 PortProtocolsHTTP, TCP/IP, UDP, ICMP, SMTP, DHCP, DNSStream2x StreamsWi-Fi2.4GhzLANSupportSmart PhoneiOS/AndroidGeneralDimensions(W*H*D)186.82*56.27*68.08 (mm)Weights(g)400gMaterialAluminumWorking Temperature-20°C~55°CHumidityRH 10%~90%Power SupplyDC12V/1AConsumptionDay≦3W Night≦ 6WInstallationWall/Ceiling Bracket Mounting		
Auto. White BalanceSupportImage RotationSupport (Mirror/Flip)Two-Way TalkSupportFTPNot SupportedNetwork10M/100M Ethernet, RJ45 PortProtocolsHTTP, TCP/IP, UDP, ICMP, SMTP, DHCP, DNSStream2x StreamsWi-Fi2.4GhzLANSupportSmart PhoneiOS/AndroidGeneralDimensions(W*H*D)186.82*56.27*68.08 (mm)Weights(g)400gMaterialAluminumWorking Temperature-20°C~55°CHumidityRH 10%~90%Power SupplyDC12V/1AConsumptionDay≦3W Night≦ 6WInstallationWall/Ceiling Bracket Mounting		
Image RotationSupport (Mirror/Flip)Two-Way TalkSupportFTPNot SupportedNetwork10M/100M Ethernet, RJ45 PortProtocolsHTTP, TCP/IP, UDP, ICMP, SMTP, DHCP, DNSStream2x StreamsWi-Fi2.4GhzLANSupportSmart PhoneiOS/AndroidGeneralDimensions(W*H*D)186.82*56.27*68.08 (mm)Weights(g)400gMaterialAluminumWorking Temperature-20°C~55°CHumidityRH 10%~90%Power SupplyDC12V/1AConsumptionDay≦3W Night≦ 6WInstallationWall/Ceiling Bracket Mounting		
Two-Way Talk  FTP  Not Supported  Network  Ethernet  10M/100M Ethernet, RJ45 Port  HTTP, TCP/IP, UDP, ICMP, SMTP, DHCP, DNS  Stream  2x Streams  Wi-Fi  2.4Ghz  LAN  Support  Smart Phone  iOS/Android  General  Dimensions(W*H*D)  186.82*56.27*68.08 (mm)  Weights(g)  Material  Aluminum  Working Temperature  -20°C~55°C  Humidity  RH 10%~90%  Power Supply  DC12V/1A  Consumption  Day≦3W Night≦ 6W  Installation  Wall/Ceiling Bracket Mounting		
FTPNot SupportedNetworkNetworkNetworkEthernet10M/100M Ethernet, RJ45 PortProtocolsHTTP, TCP/IP, UDP, ICMP, SMTP, DHCP, DNSStream2x StreamsWi-Fi2.4GhzLANSupportSmart PhoneiOS/AndroidGeneralDimensions(W*H*D)186.82*56.27*68.08 (mm)Weights(g)400gMaterialAluminumWorking Temperature-20°C~55°CHumidityRH 10%~90%Power SupplyDC12V/1AConsumptionDay≦3W Night≦ 6WInstallationWall/Ceiling Bracket Mounting		
NetworkEthernet $10M/100M$ Ethernet, RJ45 PortProtocols $HTTP$ , $TCP/IP$ , $UDP$ , $ICMP$ , $SMTP$ , $DHCP$ , $DNS$ Stream $2x$ StreamsWi-Fi $2.4Ghz$ LANSupportSmart Phone $iOS/Android$ General $Dimensions(W^*H^*D)$ $186.82^*56.27^*68.08$ (mm)Weights(g) $400g$ MaterialAluminumWorking Temperature $-20^{\circ}C\sim55^{\circ}C$ Humidity $RH\ 10\%\sim90\%$ Power Supply $DC12V/1A$ Consumption $Day \le 3W$ Night $\le 6W$ Installation $Wall/Ceiling$ Bracket Mounting		
Ethernet $10M/100M$ Ethernet, RJ45 PortProtocolsHTTP, TCP/IP, UDP, ICMP, SMTP, DHCP, DNSStream $2x$ StreamsWi-Fi $2.4$ GhzLANSupportSmart Phone $iOS/Android$ GeneralDimensions(W*H*D) $186.82*56.27*68.08$ (mm)Weights(g) $400g$ MaterialAluminumWorking Temperature $-20^{\circ}C\sim55^{\circ}C$ HumidityRH $10\%\sim90\%$ Power SupplyDC12V/1AConsumption $Day \le 3W$ Night $\le 6W$ InstallationWall/Ceiling Bracket Mounting		Not Supported
ProtocolsHTTP, TCP/IP, UDP, ICMP, SMTP, DHCP, DNSStream2x StreamsWi-Fi2.4GhzLANSupportSmart PhoneiOS/AndroidGeneralDimensions(W*H*D)186.82*56.27*68.08 (mm)Weights(g)400gMaterialAluminumWorking Temperature-20°C~55°CHumidityRH 10%~90%Power SupplyDC12V/1AConsumptionDay≦3W Night≦ 6WInstallationWall/Ceiling Bracket Mounting		10M/100M Ethornot P I/15 Port
ProtocolsStream $2x$ StreamsWi-Fi $2.4$ GhzLANSupportSmart Phone $iOS/Android$ GeneralDimensions(W*H*D) $186.82*56.27*68.08$ (mm)Weights(g) $400g$ MaterialAluminumWorking Temperature $-20^{\circ}C\sim55^{\circ}C$ HumidityRH $10\%\sim90\%$ Power Supply $DC12V/1A$ Consumption $Day \le 3W$ Night $\le 6W$ InstallationWall/Ceiling Bracket Mounting	Ethernet	
Stream         2x Streams           Wi-Fi         2.4Ghz           LAN         Support           Smart Phone         iOS/Android           General         Dimensions(W*H*D)           Dimensions(W*H*D)         186.82*56.27*68.08 (mm)           Weights(g)         400g           Material         Aluminum           Working Temperature         -20°C~55°C           Humidity         RH 10%~90%           Power Supply         DC12V/1A           Consumption         Day≦3W Night≦ 6W           Installation         Wall/Ceiling Bracket Mounting	Protocols	
Wi-Fi         2.4Ghz           LAN         Support           Smart Phone         iOS/Android           General         Image: Consumption           Dimensions(W*H*D)         186.82*56.27*68.08 (mm)           Weights(g)         400g           Material         Aluminum           Working Temperature         -20°C~55°C           Humidity         RH 10%~90%           Power Supply         DC12V/1A           Consumption         Day≦3W Night≦ 6W           Installation         Wall/Ceiling Bracket Mounting	Stream	·
	Wi-Fi	
$\begin{tabular}{lll} Smart Phone & iOS/Android \\ \hline General & & \\ \hline Dimensions(W*H*D) & 186.82*56.27*68.08 (mm) \\ \hline Weights(g) & 400g \\ \hline Material & Aluminum \\ \hline Working Temperature & -20^{\circ}C\sim55^{\circ}C \\ \hline Humidity & RH 10\%\sim90\% \\ \hline Power Supply & DC12V/1A \\ \hline Consumption & Day $\leq$ 3W Night $\leq$ 6W \\ \hline Installation & Wall/Ceiling Bracket Mounting \\ \hline \end{tabular}$		_
General           Dimensions(W*H*D)         186.82*56.27*68.08 (mm)           Weights(g)         400g           Material         Aluminum           Working Temperature         -20°C~55°C           Humidity         RH 10%~90%           Power Supply         DC12V/1A           Consumption         Day≦3W Night≦ 6W           Installation         Wall/Ceiling Bracket Mounting	Smart Phone	
Dimensions(W*H*D)         186.82*56.27*68.08 (mm)           Weights(g)         400g           Material         Aluminum           Working Temperature         -20°C~55°C           Humidity         RH 10%~90%           Power Supply         DC12V/1A           Consumption         Day≦3W Night≦ 6W           Installation         Wall/Ceiling Bracket Mounting		
Weights(g)       400g         Material       Aluminum         Working Temperature       -20°C~55°C         Humidity       RH 10%~90%         Power Supply       DC12V/1A         Consumption       Day≦3W Night≦ 6W         Installation       Wall/Ceiling Bracket Mounting		186.82*56.27*68.08 (mm)
Material       Aluminum         Working Temperature       -20°C~55°C         Humidity       RH 10%~90%         Power Supply       DC12V/1A         Consumption       Day≦3W Night≦ 6W         Installation       Wall/Ceiling Bracket Mounting		` ,
Working Temperature         -20°C~55°C           Humidity         RH 10%~90%           Power Supply         DC12V/1A           Consumption         Day≦3W Night≦ 6W           Installation         Wall/Ceiling Bracket Mounting		ŭ
Humidity       RH 10%~90%         Power Supply       DC12V/1A         Consumption       Day≦3W Night≦ 6W         Installation       Wall/Ceiling Bracket Mounting		
Power Supply       DC12V/1A         Consumption       Day≦3W Night≦ 6W         Installation       Wall/Ceiling Bracket Mounting		
Consumption       Day ≦ 3W       Night ≦ 6W         Installation       Wall/Ceiling Bracket Mounting		
Installation Wall/Ceiling Bracket Mounting		
Ŭ Ŭ	<u> </u>	, ,
LAN		vvaii/Ceiiiig Diacket Woullting
	LAN	l