

STEPPING MOTORS

PX243, PX244, PX245 type

Step Angle 1.8°

■ Features

— Installing Base Size 1.65" sq.



■ Specifications

Motor		Voltage V. DC	Current per Phase A/Phase	Holding Torque		Resistance per Phase ohm/Phase	Inductance per Phase mH/Phase	Rotor Inertia		Number of Leads
Single Shaft	Double Shaft			OZ-in	N-cm			OZ-in ²	g-cm ²	
PX243-01AA	PX243-01BA	4	0.95	15.3	10.8	4.2	2.2	0.09	16	6
PX243-02AA	PX243-02BA	9.6	0.4	15.3	10.8	24	13	0.09	16	6
PX243-03AA	PX243-03BA	12	0.31	15.3	10.8	38.5	25	0.09	16	6
PX244-02AA	PX244-02BA	6	0.8	22.2	15.7	7.5	6.5	0.13	24	6
PX244-03AA	PX244-03BA	12	0.4	22.2	15.7	30	28	0.13	24	6
PX244-04AA	PX244-04BA	24	0.2	22.2	15.7	120	105	0.13	24	6
PX245-01AA	PX245-01BA	4	1.2	30.5	21.5	3.3	2.4	0.19	35	6
PX245-02AA	PX245-02BA	6	0.8	30.5	21.5	7.5	5.8	0.19	35	6
PX245-03AA	PX245-03BA	12	0.4	30.5	21.5	30	22	0.19	35	6

■ Colors of Lead Wires

● 6-Lead Wires

