



IPC-Touch15P

Datasheet

Dimension	384W x 312H x 44.5D mm
Case Material	ABS front frame + SECC
Weight	4 Kg
Mounting Spec.	VESA 75 / 100
Panel Frame Water Proof	IP65
Optional Accessory	Wall Mount Kit / Stand
Max Resolution	XGA 1024 x 768
Color Support	16.2M / 262K colors
Max Sync Rate (V x H)	60 Hz x 80 kHz
Response Time	2.3 ms(Falling time) 5.7 ms(Raising time)
Controls / Adjustments	Color : Contrast,Brightness, Color temperature Image : H-Position, V-Position, Clock OSD : OSD H-Position/V-Position, OSD Time, Reset, Language
OSD Languages	Traditional Chinese , Simplified Chinese , English, Spanish , Japanese , French , German
Backlight Life	50,000 hours
Touch Screen	AMT 5 wires Resistive Touch screen
Image Aspect Ratio	4:3
Brightness	350
Contrast Ratio	700:1
H-View Angle	160°
V-View Angle	140°
Signal Interfaces	VGA / DVI, USB / RS232 (Optional)
Cables Included (Length: 1.8M)	VGA Cable x 1, RS-232 Cable x 1
Voltage Required	DC 12V
Power Consumption Operational	1.02A max.
Operating Temperature	-20 °C ~ 60 °C
Operation Humidity Range	5~90 %RH@39 °C, non-condensing
Storage Temperature	-20 °C ~ +65 °C
Storage Humidity Range	5~90 %RH@39 °C, non-condensing