

Medi@link Black Panther Cable HD, 1CI + 1 card



RoHS
Support

*Medi@link digital Quality at Environment in Mind
with ECO Friendly Materials*

1W stand-by
*Energy-saver
Energie-sparer*

Full HD
1080

SATVISION

Medi@Link Black Panther

GUT

ID-Receiver mit Pay-TV-Funktion - 10/2011
Todeskopierschutz TV-zul. UK-Entfernung



1CI + 1Card



Cable included



Black Panther



Medi@link
Black Panther

1CI + 1Card

1CI + 1Card

HD TV

HDTV

HI-SPEED CERTIFIED USB

USB

HDMI

HDMI

Ethernet

Ethernet

1W stand-by

1W standby

IPTV

SUPPORT

RoHS CE



 TV
  MOVIE
  MUSIC
  PHOTO
  JPEG
  SUBTITLE
  TELETEXT
  SWUPDATE
  Ethernet
  HD
  DOLBY
  USB
  HD 1080i
  HDMI
  1CARD
  1CI
  IPTV

Feature

Fully compatible to MPEG-2/ MPEG-4
1 Common Interface
1 Smart card reader
Ethernet interface for up-to-date software upgrade
Portable 12 V support
(Output 12V / input AC100-240V)
User friendly & Multi-languages MENU
Max. 10,000 channels in TV and Radio
7 favorite channels lists
Software update via Network or USB memory stick
MP-3 and JPEG photo album compatible
7 day and program guide
Blind scan
Pre-Installation
Timer control function (Automatic ON / OFF)
Subtitle supports
Teletext supports
(DVB ETS 300 706 & VBI Insertion)
Powerful channel editing and upgrade via USB

TECHNICAL SPECIFICATIONS

TUNER

Input Frequency	44 ~ 1002MHz
FEC Decoder	Reed-Solomon
Demodulation	16 QAM, 32 QAM, 64 QAM, 128 QAM, 256 QAM
Input Impedence	75Ω
Input Connector	F Female (RF IN/OUT) / IEC Male, IEC Female

NETWORK

Ethernet	RJ-45(10/100BASE-T)
----------	---------------------

VIDEO/AUDIO DECODING

Video Decoding	MPEG2 SD/HD, MPEG4, H.264/AVC SD/HD
Audio Decoding	AAC, AC3, WMA, MPEG-1 and -2, layer 1 and 2, MP3, MPEG-4 HE-AAC V1L1, L2, V2 L2/L4

Front & Rear Panel I/O

Display	VFD Display
Front	3 Button (Power, Up, Down) IR Module (38KHz)
Rear	Composite (CVBS) x 1 Component (Y/Pb/Pr) x 1 Optical S/PDIF x 1 USB 2.0 x 1 RJ-45 x 1 SCART (TV) x 1 DC Jack x 1
Smartcard	x 1
Common Interface	x 1

Physical Specifications

Dimension	240 x 150 x 45 (mm)
Gross Weight	1.88Kg
Powersupply	DC 12V (Adapter)
Power Consumption	1W by Standby mode

