

HDB15M
(BEIGE COLOR)

HDB15M
(BEIGE COLOR)


ITEM NO	COLOR	LENGTH	NO.
CV0026	BEIGE	3000±30mm	4260113564585
CV0027	BEIGE	5000±50mm	4260113564592
CV0028	BEIGE	10000±100mm	4260113564608
CV0034	BEIGE	1800±20mm	4260113568743

PACKING:1PCS/PE BAG+LABEL

NOTE:

1. CABLE: 30AWG, NON-UL, AL-FOIL, 14C+1, OD=6.0±0.2mm, BEIGE COLOR, PVC JACKET.
2. LENGTH: L.
3. CONNECTORS: HDB15P*2PCS (BLUE INSULATION) (NOT 9PIN) (SHELL NICKEL).
4. SCREW: INCH SCREW*4PCS (NICKEL).
5. CONTACTS:

HDB15P	1	2	3	4	5	6	7	8	X	10	11	12	13	14	15	64
HDB15P	1	2	3	4	5	6	7	8	X	10	11	12	13	14	15	64
6. MOLD: ASS'Y IBM TYPE.
7. OPEN/SHORT TEST: 100% TEST.
 A. 100% OPEN, SHORT & INTERMITTANCE TEST.
 B. CONDUCTOR RESISTANCE: 30hms MAX.
 C. INSULATION RESISTANCE: 5M Min./10ms:
8. ALL MUST BE ROHS COMPLIANT.



LABEL

COMPANY	2D		ITEM NO.	CV0026	ND	B6123	Part Name	HDB15MM 14C+1		
REVISION	DATE	DISCRIPTION	DRAWN BY							
REV.A/0	2011.12.25	T8-1112011	DESIGNED BY							
			APPROVAL BY							
				SPEC	2direct GmbH					
SCALE		NON		UNIT (mm)		PAGE		1/1		