

NOTES:

TECHNICAL CHARACTERISTICS:

1. VIBRATION: 100M/S<sup>2</sup> (10~500HZ)
2. IMPEDANCE: 75 Ω
3. FREQUENCY RANGE: DC~1GHZ
4. WORKING VOLTAGE: 170V MAX
5. WITHSTAND VOLTAGE: 500V RMS

CONTACT RESISTANCE:

1. CENTER CONTACT: ≤ 10 MΩ
2. OUTER CONTACT: ≤ 5 MΩ
3. INSULATION RESISTANCE: ≥ 1000 MΩ
4. VSWR : STRAIGHT: ≤ 1.20, RIGHT ANGLE: ≤ 1.30
5. DURABILITY (MATING): ≥ 500 TIMES MIN;


ENVIRONMENTAL:

1. STORAGE: -40° TO +85°
2. OPERATION: 0° TO 70°

MATERIAL: ABS; COPPER (CU)

**Keystone Module SAT/antenna**

- 16.2 mm width, Coaxial female > F female
- for installation in the KeyStone patch panels, wall sockets, housing and so on
- plastic housing

Änderungen		Datum	Name	Bezeichnung	Blatt
Datum	Name	gez.: 04.03.2020	nw	Keystone Module SAT/antenna 	
		gepr.: 04.03.2020	nw		
		Norm:		Zeichnungs-Nr.: 79936	von
Änderungen vorbehalten / Subject to change					