**399 0%** SR927W (SR57) Watch Battery Swiss Made

## **Technical Data Sheet**

## Specifications


Chemical system Nominal Voltage Capacity Operating Temperature\* Self Discharge Weight

Zinc / Monovalent Silver Oxide, high drain 1,55 V 53 mAh, Discharge over 15 k $\Omega$  at 20°C to 0,9 V -10°C – 60°C Less than 10% per year at 20°C ~0,73 g

## Dimensions


(according IEC 60086-3)

Diameter	9,50 mm (0,374")
Height	2,70 mm (0,106")



## **Discharge Curve**

Constant Load	15 k $\Omega$
Starting Drain	101 μA
Temperature	20°C



\*Condensing humidity not allowed

Information and contents in this data sheet are for reference purpose only. They do not constitute any warranty or representation and are subject to change without notice. For most current information and further details, please contact your Renata representative. For safety related information please consult the PSDS document related to that product or product family. The Products of Renata SA are neither designed nor authorized for use in certain areas of application of environment. For further details we refer to our webpage <a href="https://www.renata.com/downloads/restriction\_of\_use">www.renata.com/downloads/restriction\_of\_use</a>

Rev. 399MF.05 2019/08

Renata SA CH-4452 Itingen/Switzerland Tel. +41 (0)61 975 75 75 Fax. +41 (0)61 975 75 95 sales@renata.com www.renata.com

