Art No. PL0008

500Mbps Powerline Ethernet Mini Adapter, Duo Pack

ogiLink

HD entertainment and fast home network in one: with speeds of 500 Mbps, the Powerline PL0008 is powerful enough to transmit even 3D movies to every room of your home. Without routing cables or WLAN picture stutter - simply over the electrical wiring. Connect computers, laptops, game consoles as well as Internet TVs and hard drive recorders to each other and to the Internet. The first powerline adapter of the latest generation is fully compatible with all 200 AV adapters, is extremely energy saving and, thanks to its flat, inconspicuous design, can be positioned anywhere.

Features:

LogiLink.

.

- IEEE1901 and HomePlug AV Compliant
- Co-existence with HomePlug 1.01
- High transfer rate of up to 500 Mbps
- For all types of bandwidth-intensive transmission
- High Definition (HD) and Standard Definition (SD) video distribution
- Internet Protocol Television (IPTV) distribution
- Home networking backbone for Wi-Fi, and Wireless USB
- High speed broadband sharing
- Audio and video streaming and internet downloading
- PC files and applications sharing
- Printer and peripheral sharing
- Network and interactive online gaming
- Security cameras
- Supports low power "Standby" mode for 2013 EuP Standard
- Full compatibility with all 200 and 500 HomePlug AV adapters





RoHS



Art No. PL0008

500Mbps Powerline Ethernet Mini Adapter, Duo Pack

LogiLink.

Specification:

LogiLink.

111111

•0 •6

Frequency band 2 – 68 MHz (With Mask) Modulation OFDM (Supports OFDM 4096/1024/256/64/16/8- QAM, QPSK, BPSK and ROBO Modulation Schemes) FEC (Forward Error Correction) Coding Frequency Notching support PHY Rate: 500Mbps TCP: Up to 97 Mbps effective throughput
UDP: Up to 97 Mbps effective throughput
TDMA and priority-based CSMA/CA channel access schemes maximize efficiency and throughput
Integrated Quality of Service (QoS) Enhancements
Hardware Packet Classifiers for ToS, CoS and IP Port Number
Supports IGMP managed multicast sessions
Auto-MDI/MDI-X negotiation and sensing for 10/100 Ethernet
4 Levels priority based contention access and multi segment
bursting
8 Levels VLAN priority field
Up to 15 slaves with 1 master, 16 total devices
It supports max. 8 nodes at home
Supports IGMP managed multicast sessions
Hardware Packet Classifiers for ToS, CoS and IP Port Number
128-bit AES Link Encryption with key management
AC Wire; 200 meter
IEEE 802.3, IEEE 802.3u, HomePlug AV 1.01, IEEE 802.1p, IEEE 1901
Network Setup button for Network Security Management and
Factory default reset button









LogiLink.

One 10/100 Ethernet RJ45 port Power Supply: 100-240 VAC 50/60Hz
Power Supply: 100-240 VAC 50/60Hz
Power Consumption: 4W Max. (Standby Mode: 0.45W)
Window 98SE/Me/NT2000/XP/Vista/Win 7, MAC and Linux
Operating Temperature: 0~45°C
Preserve Temperature: 0~70°C
Operating: 10~90% non-Condensing
Preserve: 10~95% non-Condensing
Dimensions (L x W x H): 67x50x32 mm (With Plug)
Weight: 97g (Wall Mount Type)
Power (Green, Blinking at standby mode)
Link (Green/Orange/Red throughput indicator)
Ethernet (Green)

Art No. PL0008


ogiLink

Package Content:

- 2 x Powerline Ethernet Adapters
- 2 x CAT5e Cable, 1.2M
- 1 x Quick Installation Guide
- 1 x CD (Software & Manual)

Packaging Information:

- Packing Dimension: mm
- Packing Weight: kg
- Carton Dimension: mm
- Carton Q'ty: pcs
- Carton Weight: kgs



RoHS CE



* The specifications and pictures are subject to change without notice. *All trade names referenced are the registered namework of their respective owners.