Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria

Model identifier: 218600

Type of light source:					
Lighting technology used:	LED	Non-directional or directional:	NDLS		
Light source cap-type	Connector				
(or other electric interface)					
Mains or non-mains:	NMLS	Connected light source (CLS):	No		
Colour-tuneable light source:	No	Envelope:	-		
High luminance light source:	No				
Anti-glare shield:	No	Dimmable:	Yes		
Product parameters					
Parameter	Value	Parameter	Value		
General product parameters:					
Energy consumption in on- mode (kWh/1000 h), rounded	4	Energy efficiency class	Е		

mode (kWh/1000 h), rounded		class	
up to the nearest integer			
Useful luminous flux (фuse), in-	500 in	Correlated colour	40006500
dicating if it refers to the flux in	Sphere (360°)	temperature,	

a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	Sprici (300)	rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	
On-mode power (P _{on}), ex-	4,0	Standby power (P _{sb}),	0,00

			tilat call be set	
On-mode pow pressed in W	ver (P _{on}), ex-	4,0	Standby power (P _{sb}), expressed in W and rounded to the sec- ond decimal	0,00
	andby power expressed in W the second dec-	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	90
Outer dimen-	Height	40	Spectral power dis-	See image
sions without	Width	121	tribution in the	in last page
separate con-	Danth	4.45	range 250 nm to 800	

			acs that can be set	
Outer dimen-	Height	40	Spectral power dis-	See image
sions without	Width	121	tribution in the	in last page
separate con-	Depth	445	range 250 nm to 800	
trol gear, light-	Верин	443	nm, at full-load	
ing control				

parts and non- lighting con- trol parts, if any (millime- tre)			
Claim of equivalent power ^(a)	-	If yes, equivalent power (W)	-
		Chromaticity coordi-	0,440
		nates (x and y)	0,403
Parameters for LED and OLED light sources:			
R9 colour rendering index value	56	Survival factor	1,00
the lumen maintenance factor	0,98		

(a)'-': not applicable; (b)'-': not applicable;

