




FTTH Termination Box 1 x LCD/APC with Installation Cable


Technical Features

Fiber to the home termination box, fully assembled Box 80 x 80 mm with 1x LCD/APC adapter With 2-core breakout cable Prefabricated on one side with pigtail 2x LC/APC Flame retardant and halogen-free, B2ca-s1a, d0, a1 Compliant with EN 50575:2014+A1:2016

Art No.	Length	EAN Code
FB2LC20	20 m	4052792071610
FB2LC30	30 m	4052792071627
FB2LC40	40 m	4052792071634
FB2LC50	50 m	4052792071641
FB2LC60	60 m	4052792071658

Technical Drawings







Test:			
TYPE	Single-Mode		
Insertion Loss	≤0.3dB (IEC 61300-3-4)		
Return Loss	APC≥60dB (IEC 61300-3-6)		
Test Wavelength	1310nm		


www.2direct.de


*The specifications and pictures are subject to change without prior notice. *All trade names referenced are the registered trademarks of their respective owners.














Package Content

1x FTTH Termination Box

Packaging Information

Art. No.	Packing Dimension	Packing Weight	Carton Q'ty	Packing Dimension	Packing Weight
FB2LC20	250 x 235 x 50 mm	0.33 kg	10 pcs	480 x 265 x 260 mm	3.8 kg
FB2LC30	250 x 235 x 50 mm	0.378 kg	10 pcs	480 x 265 x 260 mm	4.28 kg
FB2LC40	250 x 235 x 50 mm	0.42 kg	10 pcs	480 x 265 x 260 mm	4.7 kg
FB2LC50	250 x 235 x 50 mm	0.466 kg	10 pcs	480 x 265 x 260 mm	5.16 kg
FB2LC60	250 x 235 x 50 mm	0.518 kg	10 pcs	480 x 265 x 260 mm	5.68 kg



*The specifications and pictures are subject to change without prior notice. *All trade names referenced are the registered trademarks of their respective owners.