



# HITPOINT

TEL:8862-26013311

FAX:8862-26013898

NO.4 Lane 505, Zhongzheng Rd., Linkou Shiang, Taipei, Taiwan 24445 . R.O.C

## Magnetic Buzzer PB-2015PQ

(RoHS)

DATE:2009.03.18


### 1 . Electrical Characteristics

VER .:3

Oscillation Frequency (Hz)	1500
Operating Voltage (Vp-p)	2.0 ~ 5.0
Rated Voltage (Vp-p)	3.0
Input Watt (W/max.)	0.15
Sound Pressure Level (dB/min.)	75 at 10cm at Rated Voltage
Coil Resistance ( $\Omega$ )	$8.0 \pm 2$
Operating Temperature ( $^{\circ}\text{C}$ )	-10 ~ +40
Storage Temperature ( $^{\circ}\text{C}$ )	-20 ~ +50
Condition by wave ( $^{\circ}\text{C}$ )	$260 \pm 5^{\circ}\text{C}$ / within 5sec
Condition by hand ( $^{\circ}\text{C}$ )	$350 \pm 20^{\circ}\text{C}$ / within 5sec

PS : Vp-p= 1/2duty , square wave

### 2 . Typical Frequency Response Curve





# HITPOINT


TEL:8862-26013311

FAX:8862-26013898

NO.4 Lane 505, Zhongzheng Rd., Linkou Shiang, Taipei, Taiwan 24445 . R.O.C

### 3 . Dimensions and Material

#### 3-1 Shape




Unit : mm


#### 3-2 Material

Housing	PPO plastic resin (Color : Black)
Leading Pin	Tin Plated Brass
Weight (Gram)	3.2

### 4 . Recommend Driving Circuit



The base current  $I_b$  should high enough so that it saturates the collector current of the transistor with the CB load.



# HITPOINT

TEL:8862-26013311

FAX:8862-26013898

NO.4 Lane 505, Zhongzheng Rd., Linkou Shiang, Taipei, Taiwan 24445 . R.O.C


## 5. TESTING METHOD

### • *Standard Measurement conditions*

*Temperature:25±2°C Humidity:45-60%*

### • *Acoustic Characteristics*

*The oscillation frequency, current consumption and sound pressure are measured by the measuring instruments shown below.*





# HITPOINT

TEL:8862-26013311

FAX:8862-26013898

NO.4 Lane 505, Zhongzheng Rd., Linkou Shiang, Taipei, Taiwan 24445 . R.O.C

## 6. RELIABILITY

<b>ITEMS</b>	<b>METHOD OF TEST AND MEASUREMENTS</b>	<b>PERFORMANCE</b>
<i>Coldness withstanding</i>	<i>After 98 hours of being exposed to -30℃ environment, should be returned to normal environment for 2 hours, then re-proceed to test.</i>	<i>No abnormality shall exist</i>
<i>Hotness withstanding</i>	<i>After 98 hours of being exposed to +80℃ environment, should be returned to normal environment for 2 hours, then re-proceed to test.</i>	<i>No abnormality shall exist</i>
<i>Humidity withstanding</i>	<i>After 98 hours of being exposed to 40℃ 95%RH environment in actual operation, should be returned to normal environment for 2 hours, then re-proceed to test.</i>	<i>No abnormality shall exist</i>
<i>Durability</i>	<i>Testing after 1,000 hours actual continuous operation. (at standard measurement conditions)</i>	<i>No abnormality shall exist</i>
<i>Drop withstanding</i>	<i>A natural drop from 75cm high down to the ground.</i>	<i>No abnormality shall exist</i>
<i>Vibration withstanding</i>	<i>Vibration of 2,000 cycles per minute, 2mm amplitude, applied in X, Y and Z directions for 30 minutes each.</i>	<i>No abnormality shall exist</i>

## 7. PACKAGE METHOD

<1> 250pcs per box , Total 10 boxes per carton , total 2500pcs carton;  
Volume: L\*W\*H=520\*335\*290mm

<2>N . W . : 8KGS ; G . W . : 9.2KGS ;

<3> RoHS Mark: