


- A) Innenleiter / Conductor 11/0.20TC
- B) Isolation PVC Rot/Schwarz/ Isulation PVC Red/Black
- C) Kabelmantel / Jacket OD:3.5±0.10mm Schwarz/ Black.22AWG 2C Cable Spec..




| Artikel Nr./ Item No. | Länge / Length (L) | Maße / Dimensions (A x B) |
|--------------------------|-----------------------|---------------------------------|
| 55154 | 0,5m | 5,5 x 2,5 mm |
| 55155 | 1m | 5,5 x 2,5 mm |
| 55156 | 1,5m | 5,5 x 2,5 mm |
| 55157 | 0,5m | 5,5 x 2,1 mm |
| 55158 | 1m | 5,5 x 2,1 mm |
| 55159 | 1,5m | 5,5 x 2,1 mm |

USB-DC Kabel / USB-DC Cable

- 1) Stecker/ Connector: USB A Male, Vernickelt/ Nickle-Plated
- 2) Stecker/ Connector: DC Male, Vernickelt/ Nickle-Plated
- 3) Kabel/ Cable NO UL 24#(11/0.16TC)*2C OD3.5mm Farbe/Color: Schwarz/ Black, PVC Kabelmantel/ Jacket

- Konformität/ Conformity: Reach/RoHS konform/ compliant

Änderungen

| Änderungen | | Datum | Name | Bezeichnung | Blatt |
|--|------|--------|------------|--|---|
| Datum | Name | gez.: | 10.10.2019 | USB-DC Kabel / USB-DC Cable |  |
| | | gepr.: | 10.10.2019 | | |
| | | Norm: | | | |
| Änderungen vorbehalten / Subject to change | | | | Zeichnungs-Nr.: | von |
| | | | | 55154, 55155, 55156, 55157, 55158, 55159 | |