

TECHNICAL DATA SHEET

www.quadrios.de

Polyester Braided Sleeving

No.: 2201CA137...141 / 22CA162...166



This cable bundling sleeve is the optimal and cost-effective solution when it comes to protecting and bringing together cables and wires. This flexible cable sleeving can also be used as an abrasive protection and as an inhibitor of animal bites. The tightly woven braid hugs the contents and keeps them together, protected and clean. The material is weather resistant, durable and looks good doing it! The application is very simple and can be customized by shortening to the desired length. The cut can be made using the hot cutting method or by means of scissors / string cutter and subsequent heat sealing of the open ends. It is possible to lead out individual cables on the track through the slot.

To prevent fraying, the sleeve should be cut with a hot cutting tool!

Technical data: Material: polyester braid • Temperature range: -55 ... 155 °C • Melting temperature: 230 °C • Color: black • Tensile strength max. 10.4 MPa • RoHS compliant, REACH compliant, halogen free • Flammability class: UL94HB

Part No.	GTIN	Content	Bundle \varnothing min.	Bundle \varnothing max.	Complete reel Part No. (content)
2201CA137	4260732280538	2 m	3 mm	4 mm	22CA162 (100 m)
2201CA138	4260732280545	2 m	6 mm	7 mm	22CA163 (100 m)
2201CA139	4260732280552	2 m	9 mm	10 mm	22CA164 (100 m)
2201CA140	4260732280569	2 m	13 mm	14 mm	22CA165 (100 m)
2201CA141	4260732280576	2 m	19 mm	20 mm	22CA166 (50 m)

This is a publication by Quadrios GmbH • Bahnhofstraße 16 • D-92670 Windischeschenbach (www.quadrios.de)

All right including translation reserved. Reproduction by any method or the capture in electronic data processing system require the prior written approval by the editor. Reprinting, also in part, is prohibited. This publication represents the technical status at the time of printing.