



GEARBOX DATA(REF):

1	Rated Voltage	12.0 VDC	2	Idle Current	100 mA Max
3	Idle Speed	222±15% rpm	4	Rated Torque	300 g. cm
5	Rated Speed	185±15% rpm	6	Rated Current	300 mA Max
7	Permit Max Torque	0.9kg. cm	8	Idle Noise	56dB(A) Max
9	Gear Ratio	100:1			

Noise Test Method: Detector with sponge to gearbox side 20cm in ambient noise under 32dB.

TECHNICAL REQUIREMENTS:

- 1.No defects such as crack, scratch, burr and deformation
- 2.No abnormal noise during testing.
- 3.RoHS compliant.

APPROVAL

产品名称	金属齿轮箱	未注公差	产品代码	ZWMC012010-100-01
客户名称	784	TOLERANCE TABLE (mm)	共 1 张	版本
设计	南奋勇 2015-02-05	IT 11	第 1 张	比例
审核		IT 12		1:1
批准		0-3 0.06 0.10	符合《ROHS相关禁止物质标准》	
		3-6 0.075 0.12	ZHAOWEI 兆威	
		6-10 0.09 0.15		
		10-18 0.11 0.18		
		18-30 0.13 0.21		
		30-50 0.16 0.25		