

Anker A1723

# Anker SOLIX C300X Portable Power Station

288Wh | 300W

InfiniPower™ SurgePad™



# Highlights

## **InfiniPower™ 10 Years of Everyday Use**

LiFePO4 batteries offer a 6× longer lifespan than the average power station. Designed for a decade of daily use, with an industry-leading 5-year device warranty

## **140W Two-Way Fast Charging**

Use the dual 140W PD 3.1 USB-C to power up two 16" Macbook Pros from 0% to 50% in just 40 minutes. Can recharge this power station to 100% within 68 minutes with ports as well.

## **Appliances Compact and Powerful in One**

Equipped with a total 360W output and a 90,000 mAh (288Wh) battery, this unit features 8 ports (3 AC, 1 USB-A, 3 USB-C and car socket), allowing you to power multiple essential devices and tablets on the go.

## **UPS 10ms**

Ensure continuous power with uninterruptible power supply(UPS) switchover time is under 20ms

## **Worry-Free Outdoor day and night**

Pair up with 100W solar panels to recharge during the day, and enjoy nighttime activities with the built-in stretchable camping light, while also charging your essential devices.

## **Remote operation is hassle-free indoors and outdoors with Wi-Fi and Bluetooth**

Using the Anker app, you can monitor and control the Anker SOLIX C300X Portable Power Station with real-time visuals and set your preferred discharge limit, battery level, recharging speed, AC timing, screen brightness, and screen time.

# Specifications

## Product Model

PN	A1723
Model Name	Anker SOLIX C300X Portable Power Station

## Battery Info

Type of Battery	LiFePO4
Capacity	288Wh
Capacity	90000mAh
Cycle Life	3000+ (to 80%)



# Specifications

## Power Outputs

Maximum Output 360W

# of Output Ports 8 (For US/CA/JP)  
7 (For EU/UK)

# of Standard AC Socket 3 (For US/CA/JP)  
2 (For EU/UK)

AC Rated Power 300W

AC Surge Power 600W

AC Auto Shut-Off Standby mode 2h

# of USB-A Output 1

USB-A Rated Power (per port) 5V=2.4A (12W Max)

USB-A Total Output 12W

# of USB-C Output 3

USB-C Rated Power (per port) 5V=3A (15W)  
5V=3A/ 9V=3A/15V=3A/  
20V=3A/28V=5A (140W Max)  
5V=3A/ 9V=3A/15V=3A/  
20V=3A/28V=5A (140W Max)

USB auto shut-off Yes

# of Car Outlet 1

Car Outlet Rated Power (per port) 10.8~14V=10A (120W Max)

# Specifications

## Power Inputs

Input Voltage	100V (JP) 120V (US/CA) 230V (EU/UK)	EST DC Adapter Recharge Time :	No
Total Input Power	330W (AC Direct)	DC Input Size	XT-60
EST Recharge Time	AC recharging: 68min(330W) PD: 142mins(140W) Solar recharging: 194mins(100W)	Solar Input Power	11-28V= 8.2A(100W Max)
Use Ports While Recharging	Yes	EST Solar Recharge Time	194mins (1*100W)
Direct AC Input	Yes	Solar Panel Compatible	Yes
Maximum AC Input Power	360W	MPPT Support	Yes
# of DC Input	1		
DC Adapter	No		

Sales Market: US/CA/JP/EU/UK

# Specifications

## Illumination Information

Flash Light	-
Flash Light Mode	-
Ambient Light	Yes
Ambient Light Mode	Ambient Light Mode (3 Level) SOS Mode

## Safety Information

Operation Temperature (°C/°F)	Charging: -20 -40°C / -4 -104°F Recharging: 0-40°C / 32-104°F
Overload Protection (AC)	>600W
Over-current Protection (USB-A)	>3A
Over-current Protection (USB-C)	>6A
Over-current Protection (Car Port)	>12.8A

## Package Content

AC Adapter	-
Cable	AC Charging Cable 80cm

## Weight & Dimension

Product Dimension	164*161*240mm 6.5x6.3x9.5in
Product Weight	4 kg ; 8.82 lb