



- USB 3.0 SUPER SPEED KABEL
 - USB A-Stecker > USB A-Buchse
 - Bitrate: bis zu 5Gb/s
 - Schirmung: 3-fach
 - Isolationswiderstand: 300V 10MOhm
 - Spannungsfestigkeit: AC 150V~/s, 1mA
 - Kabelaufdruck: E324703 **FW**
 - AWM STYLE 2725 80°C 30V
 - Kontaktwiderstand: 30Ohm
 - Innenleiter: AWG 28, Cu
 - Isolation: 88A PVC
 - RoHS-konform
-
- USB 3.0 SUPER SPEED CABLE
 - USB A plug > USB A jack
 - Bit rate: up to 5Gbps
 - Shielding: 3 times
 - Insulation resistance: 300V 10MOhm
 - Dielectric strength: AC 150V~/sec., 1mA
 - Imprint: E324703 **FW**
 - AWM STYLE 2725 80°C 30V
 - Contact resistance: 30Ohm
 - Inner conductor: AWG 28, Copper
 - Insulation: 88A PVC
 - RoHS compliant

Nr. / No.	Länge / Length (m)
93998	1.80
93999	3.00
95726	5.00



Änderungen		Datum		Bezeichnung		Blatt	
Datum	Name	gez.:	28.11.2013	USB 3.0 Verl AA SCHWARZ		900bay®	
		gepr.:	28.11.2013	Zeichnungs-Nr.:		von	
		Norm:					
		Änderungen vorbehalten / Subject to change					