

T-1 (3mm) SOLID STATE LAMP

L-934GD

GREEN


Features

- •LOW POWER CONSUMPTION.
- •POPULAR T-1 DIAMETER PACKAGE.
- •GENERAL PURPOSE LEADS
- •RELIABLE AND RUGGED.
- •LONG LIFE SOLID STATE RELIABILITY.
- •AVAILABLE ON TAPE AND REEL.
- •RoHS COMPLIANT.

Description

The Green source color devices are made with Gallium Phosphide Green Light Emitting Diode.

Package Dimensions



Notes:

- 1. All dimensions are in millimeters (inches).
- 2. Tolerance is $\pm 0.25 (0.01")$ unless otherwise noted.
- 3. Lead spacing is measured where the lead emerge from the package.
- 4. Specifications are subject to change without notice.

SPEC NO: DSAA6381 REV NO: V.8 DATE: APR/05/2005 PAGE: 1 OF 3

DRAWN: B.H.LI

APPROVED: J. Lu CHECKED: Allen Liu

Kingbright

Selection Guide

Part No.	Dice	Lens Type	lv (m @ 10	,	Viewing Angle
			Min.	Тур.	2 θ 1/2
L-934GD	GREEN (GaP)	GREEN DIFFUSED	8	20	60°

Note

Electrical / Optical Characteristics at Ta=25°C

Symbol	Parameter	Device	Тур.	Max.	Units	Test Conditions
λpeak	Peak Wavelength	Green	565		nm	IF=20mA
λD	Dominant Wavelength	Green	568		nm	IF=20mA
Δλ1/2	Spectral Line Half-width	Green	30		nm	IF=20mA
С	Capacitance	Green	15		pF	VF=0V;f=1MHz
VF	Forward Voltage	Green	2.2	2.5	V	IF=20mA
IR	Reverse Current	Green		10	uA	VR = 5V

Absolute Maximum Ratings at Ta=25°C

Parameter	Green	
Power dissipation	105	mW
DC Forward Current	25	mA
Peak Forward Current [1]	140	mA
Reverse Voltage	5	V
Operating/Storage Temperature	-40°C To +85°C	
.ead Solder Temperature [2] 260°C For 3 Seconds		
Lead Solder Temperature [3]	260°C For 5 Seconds	


Notes:

- 1. 1/10 Duty Cycle, 0.1ms Pulse Width.
- 2. 2mm below package base.
- 3. 5mm below package base.

SPEC NO: DSAA6381 REV NO: V.8 DATE: APR/05/2005 PAGE: 2 OF 3
APPROVED: J. Lu CHECKED: Allen Liu DRAWN: B.H.LI


 $^{1. \}theta 1/2$ is the angle from optical centerline where the luminous intensity is 1/2 the optical centerline value.


Kingbright





wavelength ヽ(nm) RELATIVE INTENSITY Vs. WAVELENGTH


Green L-934GD











Remarks:

If special sorting is required (e.g. binning based on forward voltage, luminous intensity, or wavelength), the typical accuracy of the sorting process is as follows:

- 1. Wavelength: +/-1nm
- 2. Luminous Intensity: +/-15%
- 3. Forward Voltage: +/-0.1V

Note: Accuracy may depend on the sorting parameters.

SPEC NO: DSAA6381 REV NO: V.8 DATE: APR/05/2005 PAGE: 3 OF 3
APPROVED: J. Lu CHECKED: Allen Liu DRAWN: B.H.LI