



QDC-1(26)-D

## QDC RANGE (80 V DC, 125 V DC)

### 80 V DC CIRCUIT BREAKERS 10 kA Curve U2 Mini-rail Mounting, 57 mm Escutcheon and DIN Rail Mounting, 45 mm Escutcheon

TYPE	POLES	VOLTAGE	kA	MCB WIDTH (mm)	STD PACK	RATING (A)	PRICE EA.
<b>QDC-1(13)</b> (Grey Handle)	1	80 V DC	10	13 (1 Module)	12	5	TBA
						10,15,20	TBA
						25,30,35,40	TBA
						45,50,60	TBA
<b>QDC-2(13)</b> (Grey Handle)	2	80 V DC	10	26 (2 Modules)	6	5	TBA
						10, 15, 20	TBA
						25,30,35,40	TBA
						45,50	TBA
<b>QDC-2(13)</b> (Grey Handle)	2 (Parallel)	80 V DC	10	26 (2 Modules)	6	80	TBA
						100	TBA
<b>QDC-3(13)</b> (Grey Handle)	3 (Parallel)	80 V DC	10	39 (3 Modules)	4	125,150	TBA

### 125 V DC CIRCUIT BREAKERS 10 kA Curve U2 Mini-rail Mounting, 57 mm Escutcheon and DIN Rail Mounting, 45 mm Escutcheon

TYPE	POLES	VOLTAGE	kA	MCB WIDTH (mm)	STD PACK	RATING (A)	PRICE EA.
<b>QDC-1(13)</b> (Grey Handle)	1	125 V DC	10	13 (1 Module)	12	5	TBA
						10,15,20	TBA
						25,30,35,40	TBA
						45,50,60	TBA
<b>QDC-2(13)</b> (Grey Handle)	2	125 V DC	10	26 (2 Modules)	6	5	TBA
						10,15,20	TBA
						25,30,35,40	TBA
						45,50	TBA
<b>QDC-2(13)</b> (Grey Handle)	2 (Parallel)	125 V DC	10	26 (2 Modules)	6	80	TBA
						100	TBA

### 125 V DC CIRCUIT BREAKERS 10 kA Curve U2, DIN Rail Mounting, 45 mm Escutcheon

TYPE	POLES	VOLTAGE	kA	MCB WIDTH (mm)	STD PACK	RATING (A)	PRICE EA.
<b>QDC-1(26)-D</b> (Grey Handle)	1	125 V DC	10	26 (1 Module)	6	80,100,125	TBA

Contact CBI for details.

Standard discounts are not applicable.