



**TECHNICAL REQUIREMENTS:**

- 1.No defects such as crack, scratch, burr and deformation
- 2.No abnormal noise during testing.
- 3.RoHS compliant.

**GEARBOX DATA(REF):**

1	Rated Voltage	12.0 VDC	2	Idle Current	100 mA Max
3	Idle Speed	37±15% rpm	4	Rated Torque	1500 g. cm
5	Rated Speed	30±15% rpm	6	Rated Current	300 mA Max
7	Permit Max Torque	2.5kg. cm	8	Idle Noise	56dB(A) Max
9	Gear Ratio	600:1			

Noise Test Method: Detector with sponge to gearbox side 20cm in ambient noise under 32dB.

APPROVAL

产品名称	金属齿轮箱	未注公差	产品代码	ZWMC012010-600-01	
客户名称	784	TOLERANCE TABLE (mm)		共 1 张	版本
设计	南奋勇 2014-07-25	IT 11	IT 12	第 1 张	比例
审核		0-3	0.06	0.10	1:1
批准		3-6	0.075	0.12	
		6-10	0.09	0.15	
		10-18	0.11	0.18	
		18-30	0.13	0.21	
		30-50	0.16	0.25	
		符合《ROHS相关禁止物质标准》			
		ZHAOWEI 兆威			